

## A13 UP



Technical data:	A13 75 UP	A13 82 UP
Code	8.574.1003	8.574.1004
power supply	24 V DC	24 V DC
scrubbing width	750 mm	820 mm
squeegee width	900 mm	1000 mm
max working capacity	3750 m <sup>2</sup> /h	4100 m <sup>2</sup> /h
detergent tank capacity	110 l	110 l
recovery tank capacity	130/155 l	130/155 l
traction	600W/automatic	600W/automatic
vacuum motor	1734 mmH <sup>2</sup> O/480W	1734 mmH <sup>2</sup> O/480W

### Standard equipment

#### A 13 75 UP



- 2 x 5.511.1168  
PPL brush Ø 360 mm - 14"

#### A 13 82 UP



- 2 x 5.511.1109  
PPL brush Ø 406 mm - 16"

#### A 13 75 UP



- 4.508.0646  
Front squeegee blade L.925 mm  
Shore 40 Th. 3 mm
- 4.508.0605  
Rear squeegee blade L.1015 mm  
Shore 30 Th. 4 mm

#### A 13 82 UP

- 4.508.1196  
Front squeegee blade L.1027 mm  
Shore 40 Th. 3 mm
- 4.508.1195  
Rear squeegee blade L.1150 mm  
Shore 33 Th. 4 mm



- 0.108.0054  
On-board Battery charger  
CBH2D 24V 20A

## A 13 UP

- Capable to work for the maintenance and deep cleaning of large areas (up to 4.000 m<sup>2</sup>) with a considerable reduction of cleaning costs
- More than 50 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Compact size (810 mm)
- Stability even when fully loaded, front independent wheeldrive with tight steering radius
- Recovery tank control window for cleaning and easy ordinary maintenance
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic device that stops brushes and detergent water outflow when the machine is stationary
- Antifoam device
- Self-levelling brushes
- Integrated on-board battery charger.

## Floor scrubber-driers



The easy access to the recovery tank allows fast cleaning and sanitification of the tank; the tilting tank together with a large size drain hose allow the complete emptying of the tank and the removal of any type of solid dirt. The antifoam device protects suction motor, as well as the

electronic floating switch that stops suction when the tank is full. A13 UP is equipped with actuators for the automatic lifting of the brush plate and squeegee. Control panel is provided with hour meter, speed adjustment knob and detergent



solution low level warning light. All motors are protected by thermal breakers. The detergent water tank serves as battery compartment, allowing the housing of great capacity batteries. Battery charger and suction motor are placed

in the recovery tank; the housing of the vacuum motor allows to drastically reduce the operating noise. The ergonomic and comfortable shape of the machine allows the operator to work effortless for a long time, improving productivity.



### Optional accessories:



- 4 x 0.107.0004  
Tubular battery Pb-acid  
6V 180Ah C5



- 4 x 0.107.0072  
GEL Battery 6 MFP 180  
6V 180Ah C5



- 4.508.0901 Polyurethane  
front blade L.925 TH.3 Sh.40
- 4.508.0900 Polyurethane  
rear blade L.1015 TH.4 Sh.40
- 4.508.1251 Polyurethane  
front blade L.1027 TH.3
- 4.508.1252 Polyurethane  
rear blade L.1150 TH.4



- 5.511.1246  
Tynex brush Ø 360 mm-14"
- 5.511.1169  
PPL 0,03 brush Ø 360 mm-14"
- 5.511.1203  
PES brush Ø 360 mm - 14"
- 5.511.1110  
Tynex brush Ø 406 mm-16"
- 5.511.1120  
PPL 0,03 brush Ø 406 mm-16"
- 5.511.1204  
PES brush Ø 406 mm - 16"



- 5.511.1592  
EWU pad driver Ø 380 mm-15"
- 5.511.1111  
EWU pad driver Ø 406 mm-16"



- 6.508.0143 - Ø 380 mm -  
15"- beige
- 6.508.0144 - Ø 380 mm -  
15"- green
- 6.508.0141 - Ø 380 mm -  
15"- black
- 6.508.0031 - Ø 406 mm -  
16"- beige
- 6.508.0038 - Ø 406 mm -  
16"- green
- 6.508.0045 - Ø 406 mm -  
16"- black