

PROFESSIONAL LINE

Ride-on floor scrubber driers

A18 R 90



Standard equipment



• 2 x 5.511.1845 PPL brush Ø 457 mm - 18"



- 4.508.1196 Front squeegee blade L.1027 mm Shore 40 Th. 3 mm
- 4.508.1195 Rear squeegee blade L.1150 mm Shore 33 Th. 4 mm



	A18 R 90
Code	8.575.0011
Power supply	24V DC
Equipped with	-
Scrubbing width	900 mm
Squeegee width	1000 mm
Max working capacity	6200 m²/h
Detergent tank capacity	140 l.
Recovery tank capacity	150-180 l.
Traction type	1000W/front motorwheel
Brush/Vacuum motor power	1250W/550 W

A18 R 90

• Suitable for maintenance and deep cleaning of medium and large areas (up to 4.500 m²) with a considerable reduction of cleaning costs • More than 60/80 kg of constant pressure on the brushes · Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine • Compact size • Stability even when fully loaded • Front independent wheel-drive with tight steering radius • Easy access to electrical components • Automatic brush plate lifting system • Automatic squeegee lifting system • Automatic squeegee lifting while reverse going • Automatic device that stops brushes and detergent water outflow when the machine is stationary • Antifoam device • Self-levelling brushes • High-performance batteries resulting in high-working efficiency.

PROFESSIONAL LINE



Ride-on floor scrubber driers



Quick lock recovery tank cap allows for fast and esy cleaning and sanification of the tank; the tilting tank together with a large size drain hose allow the complete emptying of the tank and the removal of any type of solid dirt. The antifoam device protects suction motor, as well as the

electronic floating switch that stops suction when the tank is full. Comfortable steering wheel. User friendly control panel, provided with hour meter, speed adjustment knob and detergent solution low level warning light. All motors are protected





by thermal breakers. 80 kg of continuous brush plate pressure with Self Leveling System to strongly and deeply removing any kind of dirt on any kind of floor. Strong oil-proof polyurethane wheels. 500 Ah C5 battery box allowing continuous working time

up to 5 hours. Built with strong components, A 18 have been designed to resist even to extreme stresses; the frame is made of steel profiles with a thickness varying from 5 to 12 mm, protected with a high resistance corrosion-proof paint.



Optional accessories:



0.107.0008
 Battery box Pb-acid
 24V 500Ah C5
 0.107.0011
 Gel battery box
 24V 400Ah C5



• 0.108.0003 Battery Charger 24/36V 50/60A - 220-240/50-60



4.508.1251 Polyurethane front blade L.1027 TH. 3
4.508.1252 Polyurethane rear blade L.1150 TH. 4



2 x 5.511.1848
Tynex brush Ø 457 mm-18"
2 x 5.511.1849
PPL 0,03 brush Ø 457 mm-18"
2 x 5.511.1847
PES brush Ø 457 mm-18"



• 2 x 5.511.1850 EWU pad driver Ø 457 mm-18"



- 6.508.0150 Ø 457 mm 18"- beige (5 pcs.)
- 6.508.00151 Ø 457 mm 18"- green (5 pcs.)
- 6.508.0142 Ø 457 mm -18"- black (5 pcs.)