

## A24



### Standard equipment



#### A 24 6000

- 2 x 5.511.1093  
PPL brush Ø 431 mm - 17"



#### A 24 7100

- 2 x 5.511.1097  
PPL brush Ø 483 mm - 19"



#### A 24 6000

- 4.508.0215  
Front squeegee blade L.1110 mm  
Shore 40 Th. 4 mm
- 4.508.0214  
Rear squeegee blade L.1185 mm  
Shore 30 Th. 6 mm

#### A 24 7100

- 4.508.0217  
Front squeegee blade L.1270 mm  
Shore 40 Th. 4 mm
- 4.508.0216  
Rear squeegee blade L.1345 mm  
Shore 33 Th. 6 mm

## A24

- Suitable for maintenance and deep cleaning of medium and large areas (up to 6.000 m<sup>2</sup>)
- More than 90/120 kg of constant pressure on the brushes
- Large load tank capacity, resulting in reduced number of stops and maximum use of battery charge for effective operation of the machine
- Stability even when fully loaded
- Front independent wheel-drive with tight steering radius
- Easy access to electrical components
- Automatic brush plate lifting system
- Automatic squeegee lifting system
- Automatic squeegee lifting while reverse going
- Automatic control system for brush rotation and detergent water outflow
- Antifoam device
- Self-levelling brush plate
- Hour meter
- High-performance batteries resulting in high-working efficiency.

Technical data:	A24 6000	A24 7100
Code	8.578.0008	8.578.0009
power supply	36 V	36 V
scrubbing width	870 mm	1020 mm
squeegee width	1110 mm	1250 mm
max working capacity	6090 m <sup>2</sup> /h	7140 m <sup>2</sup> /h
detergent tank capacity	200 l	200 l
recovery tank capacity	210/240 l	210/240 l
traction	front motorwheel/900W	front motorwheel/900W
vacuum motor	600W	600W
Motore spazzola	1500W	1500W

# Floor scrubber-driers



The unique anti foam device dramatically reduces the foam generation and prevents it from touching the suction motor, thus protecting its operation. The electronic floating switch stops suction when the tank is full. Large tank opening for fast and easy cleaning and sanitation.

The strong V-shaped floor squeegee made of steel profile is widely adjustable and allows to combine the operation of the rubber blades with the high suction power, to get a perfect drying result on every surface. The special filter box retains solid debris and prevents the obstruction of the suction hose.



A 24 scrubbers are easy to use thanks to the simple and user friendly controls. From the control panel the operator can adjust the maximum forward speed and the quantity of cleaning solution outflow, selecting the options most suitable to the dirt type. Job is simplified and made faster by the automatic lifting of the squeegee and of the brush plate.

Thanks to the optimal weight distribution and to the use of strong oil-proof polyurethane wheels the drive is perfect in all working conditions. The emptying of the solution water tank is quick with a simple and easy accessible mechanical tap.



## Optional accessories:



- 0.107.0009  
Battery box Pb-acid  
36V 360Ah C5



- 0.108.0003  
Battery Charger 24/36V  
50/60A - 220-240/50-60



- 4.508.1166 Polyurethane front blade L.1110 TH. 4
- 4.508.1165 Polyurethane rear blade L.1185 TH. 6
- 4.508.1167 Polyurethane front blade L.1270 TH. 4
- 4.508.0897 Polyurethane rear blade L.1345 TH. 6



- 5.511.1094  
Tynex brush Ø 431 mm-17"
- 5.511.1098  
Tynex brush Ø 483 mm-19"
- 5.511.1121  
PPL 0,03 brush Ø 431 mm-17"
- 5.511.1128  
PPL 0,03 brush Ø 483 mm-19"
- 5.511.1205  
PES brush Ø 431 mm - 17"
- 5.511.1206  
PES brush Ø 483 mm - 19"



- 5.511.1095  
EWU pad driver Ø 431 mm-17"
- 5.511.1099  
EWU pad driver Ø 483 mm-19"



- 6.508.0032 - Ø 431 mm - 17" - beige
- 6.508.0039 - Ø 431 mm - 17" - green
- 6.508.0046 - Ø 431 mm - 17" - black
- 6.508.0034 - Ø 483 mm - 19" - beige
- 6.508.0041 - Ø 483 mm - 19" - green
- 6.508.0048 - Ø 483 mm - 19" - black