

Wet & dry vacuum cleaner and injection/extraction
with foam cleaning device

Windy IE Foam



Equipped with:

- 2 high efficiency by-pass motors
- Suction system with by-pass cooling
- Stainless steel tank
- Detergent pump (48W - 1 l/m - 15 bar)
- Steel closing hooks
- Static electric shock inhibitor
- Fully removable tank
- 12 l. detergent tank
- Shock proof trolley
- Safety floating
- Washable cartridge filter
- 7,5 m power cable
- Traceless wheels
- Accessories Ø 40
- Equipped with connection for compressed air and pressure gauge with pressure adjuster for foam cleaning.

Standard equipment:

5.209.0021	
6.205.0197	
6.205.0205	
6.402.0108	
6.402.0109	
2 x 5.211.0102	
5.212.0141	
3.754.0048	
3.697.0072	LC Prefoam

Optional:

- 5.212.0022 - Paper collector filter set -10 pcs
- 5.209.0177 - Cloth filter for fine dust
- 5.212.0093 - Nylon filter
- 0.110.0020 - Antifoam device
- 3.697.0036 - Anti-foaming for recovery tank
- 3.697.0058 - (4x5 Kg) Acid-based det. for toilets
- 3.697.0057 - (4x5 Kg) Alkaline-based det. alimentary environments
- 3.697.0056 - (4x5 Kg) Det. for fabrics and carpeting



Watch the video on youtube:
www.youtube.com/fasavideo

Windy IE Foam

Code	8.239.0017
N° motors - power (max)	2 - 2000 (2400) W
Column depress.	22 kPa/2200 mm H ₂ O
Tank capacity	65 l.
Suction air	130 l/s
Voltage	220V-240V ~ 50-60Hz